





Løftetabel

KONECRANES | GOTTWALD Havnemobilkran G HMK 7608
150t / 74 t / 51 t

Løftekapacitet [t]														
														
Normal last	Spreader I	Spreader II	Spreader III twinlift	Spreader III	Grab	Tung last	Spreader I	Spreader II	Spreader II twinlift	Spreader III	Tung last	Sær last 	Spreader II twinlift	
Vippelastfaktor	(< 75%)	(< 75%)	(< 75%)	(< 75%)	(< 60%)	(< 75%)	(< 75%)	(< 75%)	(< 75%)	(< 75%)	(< 75%)	(< 75%)	(< 75%)	
Tilladt vindhastighed i drift [m/s]	24,6	24,6	24,6	24,6	24,6	24,6	21,4	21,4	21,4	21,4	21,4	14,3	14,3	
Radius [m]														
11	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	150,0	65,0
12	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	150,0	65,0
13	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	150,0	65,0
14	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	150,0	65,0
15	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	150,0	65,0
16	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	150,0	65,0
17	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	150,0	65,0
18	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	150,0	65,0
19	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	150,0	65,0
20	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	143,0	65,0
21	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	137,5	65,0
22	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	131,0	65,0
23	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	124,5	65,0
24	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	118,5	65,0
25	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	112,9	65,0
26	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	107,9	65,0
27	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	100,0	103,2	65,0
28	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	98,4	98,4	65,0
29	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	94,1	94,1	65,0
30	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	90,0	90,0	65,0
31	51,0	41,0	38,4	38,4	40,0	50,0	74,0	41,0	41,0	61,4	41,0	86,5	86,5	65,0
32	51,0	41,0	38,4	38,4	40,0	49,4	74,0	41,0	41,0	61,4	41,0	83,3	83,3	65,0
33	51,0	41,0	38,4	38,4	40,0	47,4	74,0	41,0	41,0	61,4	41,0	80,1	80,1	65,0
34	51,0	41,0	38,4	38,4	40,0	44,9	74,0	41,0	41,0	61,4	41,0	77,2	77,2	64,6
35	51,0	41,0	38,4	38,4	40,0	42,9	74,0	41,0	41,0	61,4	41,0	74,3	74,3	61,7
36	51,0	41,0	38,4	38,4	40,0	41,1	71,7	41,0	41,0	59,1	41,0	71,7	71,7	59,1
37	51,0	41,0	38,4	38,4	40,0	39,3	69,2	41,0	41,0	56,6	41,0	69,2	69,2	56,6
38	51,0	41,0	38,4	38,4	40,0	37,7	66,7	41,0	41,0	54,1	41,0	66,7	66,7	54,1
39	51,0	41,0	38,4	38,4	40,0	36,1	64,5	41,0	41,0	51,9	41,0	64,5	64,5	51,9
40	51,0	41,0	38,4	38,4	40,0	34,6	62,1	41,0	41,0	49,5	41,0	62,1	62,1	49,5
41	51,0	41,0	38,4	38,4	40,0	33,3	60,1	41,0	41,0	47,5	41,0	60,1	60,1	47,5
42	51,0	41,0	38,4	38,4	40,0	32,0	58,0	41,0	41,0	45,4	41,0	58,0	58,0	45,4
43	51,0	41,0	38,4	38,4	40,0	30,7	56,2	41,0	41,0	43,6	41,0	56,2	56,2	43,6
44	51,0	41,0	38,4	38,4	40,0	29,6	54,2	41,0	41,0	41,6	41,0	54,2	54,2	41,6
45	51,0	41,0	38,4	38,4	40,0	28,5	52,6	41,0	40,0	40,0	41,0	52,6	52,6	40,0
46	50,8	41,0	38,2	38,2	39,8	27,4	50,8	41,0	38,2	38,2	39,8	50,8	50,8	38,2
47	49,3	40,3	36,7	36,7	38,3	26,4	49,3	40,3	36,7	36,7	38,3	49,3	49,3	36,7
48	47,6	38,6	35,0	35,0	36,6	25,5	47,6	38,6	35,0	35,0	36,6	47,6	47,6	35,0
49	45,9	36,9	33,3	33,3	34,9	24,5	45,9	36,9	33,3	33,3	34,9	45,9	45,9	33,3
50	44,2	35,2	31,6	31,6	33,2	23,7	44,2	35,2	31,6	31,6	33,2	44,2	44,2	31,6
51	42,5	33,5	29,9	29,9	31,5	22,8	42,5	33,5	29,9	29,9	31,5	42,5	42,5	29,9
52	41,0	32,0	28,4	28,4	30,0	22,0	41,0	32,0	28,4	28,4	30,0	41,0	41,0	28,4
53	39,5	30,5	26,9	26,9	28,5	21,0	39,5	30,5	26,9	26,9	28,5	39,5	39,5	26,9
54	38,3	29,3	25,7	25,7	27,5	20,1	38,3	29,3	25,7	25,7	27,3	38,3	38,3	25,7

	spreader I	spreader II	spreader II twinlift	spreader III		spreader I	spreader II	spreader II twinlift	spreader III		spreader II twinlift
Producent:	Bromma	VDL	VDL	Bromma		Bromma	VDL	VDL	Bromma		VDL
Type:	EHSU	CH 6650 FT	CH 6650 FT	EH 180		EHSU	CH 6650 FT	CH 6650 FT	EH 180		CH 6650 FT
Egenvægt Spreader:	9,0 t	12,6 t	12,6 t	11,0 t		9,0 t	12,6 t	12,6 t	11,0 t		12,6 t
Løftekapacitet Spreader:	41 t	41 t	65 t	41 t		41 t	41 t	65 t	41 t		65 t